

ORDERING EXAMPLE

ARPEP 20 CA RO C1 MC

ARPEP

GRIPPER SWIVEL UNIT

- **ARPEP**

20

SIZE

- **16** | **20** | **25**

CA

ROTATION ANGLE VERSION

- **CA** = 180°
- **CB** = 90°

STROKE CONTROL SOLUTION *(preparation, excluded sensors)*

C-Slot included for magnetic sensors

(R626 for rotation and R793 for gripper, do not indicate codes)

- **F8** = Settable kit for M5 inductive sensor application (only for rotation)

RO

DIRECTION OF ROTATION *(consult starting condition from catalog)*

- **RO** = Clockwise
- **RA** = Anticlockwise

C1

GRIPPER STROKE VERSION

- **C1** = Short stroke, greater gripping force
- **C2** = Long stroke

MC

DEVICE TO MAINTENANCE THE GRIPPING FORCE

For version without device do not indicate codes

- **MC** = Normally closed, in case of lack of air the gripper closes
- **MA** = Normally open, in case of lack of air the gripper opens

DAMPING SOLUTION

For version without shock absorbers do not indicate codes

- **V3** = Solution with hydraulic shock absorbers

OPTIONAL

- **CM** = Magnetic sensor (indicare R793 or R626)
- **CS** = Induktive sensor
- **VMP** = Pressure maintenance valve